AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

- (canceled).
- 2. (previously presented): A vehicle running state estimation method comprising: detecting a vibration level of a portion below a spring of a running vehicle; and estimating the running state of the vehicle by determining a: least one of a condition of a road surface on which the vehicle is running and a running state of each tire,

wherein said determining is based on the detected vibration level, and wherein a waveform of time changes in the vibration level is detected and the condition of the road's irface on which the vehicle is running is estimated from a vibration level at a predetermined posi ion of the waveform or for a predetermined time range.

3. (currently amended): The Λ vehicle running state estimation method according σ claim 1, comprising:

detecting a vibration level of a portion below a spring of a running vehicle; whereir -a

frequency of the detected vibration level is analyzed to calculate a vibration level at a

predetermined frequency band and a the degree of slipperiness-concition of the road surface on which the vehicle is running is estimated from by comparing the calculated vibration level with a

1.

AMENDMENT UNDER 37 C.F.R. § 1.111 U.S. Appln. No. 10/049,509

master curve which is a vibration level detected through running on a road having a predetermined condition of a road surface of the running vehicle.

4. (currently amended): The <u>A</u>vehicle running state estimation method according to claim—1-comprising:

detecting a vibration level of a portion below a spring of a running vehicle; and
estimating the running state of the vehicle by determining a degree of slipperiness of a
road surface on which the vehicle is running and a running state of each tire.

wherein said determining is based on the detected vibration level, and wherein the frequency of the detected vibration level is analyzed, at least two vibra ion levels at different frequency bands are calculated, an operation is carried out on the at least two calculated vibration levels, and the degree of slipperiness of the road surface is estimated from computed value.

5. (currently amended): The \(\Delta\) vehicle running state estimation method comprising the comprision of a portion below a spring of a running vehicle; and estimating the running state of the vehicle by determining a condition of a road surface on which the vehicle is running and a running state of each tire.

wherein said determining is based on the detected vibration level, and necording to daim

wherein vibration levels of at least two points of a portion below the spring with a buffer member interposed therebetween are detected to calculate a vibration transmission level of the portion below the spring between the two points at a predetermined frequency band, and the degree of slipperiness condition of the road surface is estimated from the calculated vibration transmission level.

- 6. (previously presented): A vehicle running state estimation apparatus for estimating running state of a vehicle based on road surface conditions, the estimation apparatus comprising: means of detecting a vibration level of a portion below a spring of a running vehicle; means of computing waveform of time changes in the vibration level; and road surface condition estimation means for estimating a condition of a road surface on which the vehicle is running from the vibration level at a predetermined position of the waveform or for a predetermined time range.
- 7. (previously presented): The vehicle running state estimation apparatus according to claim 6 further comprising means of calculating the vibration level of at least one of a tire leading edge portion, tire ground contact portion and tire trailing edge portion of the wavelorm.
 - 8. (currently amended): A vehicle running state estimation apparatus comprising: means of detecting a vibration level of a portion below a spring of a running vehicle;

means of calculating a vibration level at a predetermined frequency band by analysing frequency of the detected vibration level; and

road surface condition estimation means for estimating a degree of slipperiness condition of the road surface on which the vehicle is running from by comparing the calculated vibration level with the master curve which is the vibration level detected through running on a road having a predetermined road surface condition.

wherein the running state of the vehicle is estimated based on the degree-of-slipper ness condition of the road surface received-from the road surface condition estimation means.

9. (previously presented): A vehicle running state estimation apparatus comprising: means of detecting a vibration level of a portion below a spring of a running vehicle; and road surface condition estimation means for estimating a degree of slipperiness of a road surface from a value obtained by carrying out an operation on at least two vibration levels at different frequency bands by analyzing the frequency of the detected vibration level.

wherein the running state of the vehicle is estimated based on the degree of slipper ness of the road surface received from the road surface condition estimation means.

10. (currently amended): A vehicle running state estimation apparatus for estimating a running state of a vehicle based on a condition of a road surface comprising:

means of detecting vibration levels of at least two points on a portion below a spring of the running vehicle with a buffer member being interposed therebet ween;

means of calculating a vibration transmission level at a predetermined frequency b ind between said at least two vibration detection points; and

road surface condition estimation means for estimating a degree of slipperiness condition of the road surface on which the vehicle is running from the calculated vibration transmiss ion level.

- 11. (canceled).
- 12. (currently amended): The A vehicle running state estimation apparatus according to claim-8, comprising:

means of detecting a vibration level of a portion below a spring of a running vehicl;

means of calculating a vibration level at a predetermined frequency band by analyzing frequency of the detected vibration level; and

road surface condition estimation means for estimating a degree of slipperiness of the road surface on which the vehicle is running from the calculated vibration level.

wherein the running state of the vehicle is estimated based on the degree of slipperi tess of the road surface received from the road surface condition estimation means, and

wherein a road surface friction coefficient μ at a time of running the vehicle is estin ated based on a relationship between a surface friction coefficient μ obtained from braking distances of the vehicle under various road conditions at different speeds and at least one of the calculated

vibration level at said predetermined frequency band and a calculated vibration transmission level.

13. (currently amended): The A vehicle running state estimation apparatus according to elaim-8.-comprising:

means of detecting a vibration level of a portion below a spring of a running vehic at means of calculating a vibration level at a predetermined frequency band by analyzing frequency of the detected vibration level; and

road surface condition estimation means for estimating a degree of slipperiness of the road surface on which the vehicle is running from the calculated vibration level.

wherein the running state of the vehicle is estimated based on the degree of slipper ness of the road surface received from the road surface condition estimation means, and wherein the frequency band is a band including frequency of natural vibration of a fire tread land portion.

14. (currently amended): The A vehicle running state estimation apparatus according to elaim 8, comprising:

means of detecting a vibration level of a portion below a spring of a running vehicle;

means of calculating a vibration level at a predetermined frequency band by analyzing frequency of the detected vibration level; and

road surface condition estimation means for estimating a degree of slipperiness of the road surface on which the vehicle is running from the calculated vibration level.

wherein the running state of the vehicle is estimated based on the degree of slippe iness of the road surface received from the road surface condition estimation means, and

wherein a threshold value is set for the vibration level, and the surface of the road is estimated to be in a low friction condition when the calculated vibration level exceeds the threshold value.

- 15. (previously presented): The vehicle running state estimation apparatus according to claim 14, wherein the threshold value can be changed.
- 16. (previously presented): The vehicle running state estimation apparatus according to claim 6 which further comprises a vehicle speed detection means to estimate the condition of a road surface based on vehicle speed.
- 17. (previously presented): The vehicle running state estimation apparatus of claim 6. further comprising:

means of judging slipperiness of the road surface based on the condition of the road surface estimated by the road surface condition estimation means; and

warning means for giving a warning when it is judged that the condition of the roac surface is slippery.

18. (previously presented): The vehicle running state estimation apparatus according to claim 17, further comprising:

vehicle speed detection means to change decision on the slipperiness of the road surface and warning level based on vehicle speed.

- 19. 24. (canceled).
- 25. (previously presented): The vehicle running state estimation apparatus according to claim 6, further comprising a transmitter for transmitting output of the vibration detection means for calculating a time change in the vibration level or a vibration level at a predetermined frequency band.
- 26. (previously presented): The vehicle running state estimation apparatus according to claim 6 further comprising a power generating unit mounted on a tire wheel, wherein the power generating unit generates power by rolling of each tire and supplies power for at least one of driving the vibration detection means and amplifying output of the vibration detection means.
- 27. (previously presented): A vehicle control apparatus comprising vehicle control means for controlling the running state of a vehicle based on the condition of the road surface estimated by the vehicle running state estimation apparatus of claim 6.

- 28. (previously presented): The vehicle control apparatus according to claim 27 which comprises vehicle speed detection means to control the running state of the vehicle based in vehicle speed.
- 29. (previously presented): The vehicle control apparatus according to claim 27, wherein the vehicle control means controls locked state of each wheel.
- 30. (previously presented): The vehicle control apparatus according to claim 27, wherein the vehicle control means controls attitude of the vehicle.
- 31. (previously presented): The vehicle control apparatus according to claim 27, wherein the vehicle control means controls air pressure of each tire.
- 32. (previously presented): The vehicle control apparatus according to claim 27, wherein the vehicle control means controls idling state of each wheel.
- 33. (previously presented): The vehicle control apparatus according to claim 27, wherein the vehicle control means changes inter-vehicle distance set value of an automatic driving system.

- 34. (previously presented): A tire wheel comprising: the vehicle running state est mation apparatus for estimating a running state of the vehicle by detecting the vibration level of the portion below the spring as set forth in claim 6, and a power generating unit for generating; power by a rolling of each tire and supplying power to the estimation apparatus.
- 35. (original): The tire wheel according to claim 34, wherein the vehicle running state estimation apparatus is mounted to the tire wheel.
- 36. (previously presented): The tire wheel according to claim 34, wherein the power generating unit comprises a rotor magnetized and rotated by the rolling of each tire, a stater made from a high magnetic permeability material and adjacent to the rotor and a power generating coil installed within a magnetic circuit including the rotor and the stator.
- 37. (original): The tire wheel according to claim 36, wherein the power generating unit comprises means of accumulating electromotive force generated in the power generating coil.
- 38. (previously presented): The tire wheel according to claim 36, wherein the rotor is turned by rotating an unbalance weight the gravity center of the rotary cone of which is extentric to a rotary shaft by the rolling of each tire.

- 39. (previously presented): The tire wheel according to claim 36, wherein an air st cam generated by the rolling of each tire is introduced into the power generating unit and the refor is turned by the introduced air stream.
- 40. (new): The vehicle running state estimation method according to claim 3, wherein the master curve is prepared based on the vibration level detected at the time when the vehicle is running on a surface of a road with a usual dry asphalt pavement.
- 41. (new): The vehicle state estimation apparatus according to claim 8, wherein th: master curve is prepared based on the vibration level detected through the running on the surface of a usual road with dry asphalt pavement.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

	☐ BLACK BORDERS
	☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
_	☐ FADED TEXT OR DRAWING
,	☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
	☐ SKEWED/SLANTED IMAGES
	☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
	☐ GRAY SCALE DOCUMENTS
	☐ LINES OR MARKS ON ORIGINAL DOCUMENT
	☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
	· · · · · · · · · · · · · · · · · · ·

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.